texlyweave®

Specification and data sheets

Woven Vinyl BreezeDécor 多用途薄贴装饰面材

Experience the Art of Comfort with Woven Vinyl BreezeDécor – Where Style Meets Innovation!

- *for flooring*
- *for wall*
- *for furniture*
- *for table top*
- *for RV & marine*
- *for elevator*
- *for DIY creativity*

© 2024 05 07 | Dragonshine - 20190901 - Any new version cancels and replaces this document

EN 15102: 2007+A1:2011
157

Material 材料: 1.0mm 25% PET 75% PVC Woven vinyl / 乙烯基編織; 650-850gsm
Backing 背底: a: 0.3mm PVC cushion 发泡革 + 0.70mm PET Nonwoven / 无纺布; 450gsm
b: 1.0mm PVC cushion / PVC 发泡革; 250gsm

woven vinyl wallcovering, product standard EN15102:2007+A1:2011

Roll dimension	Width: 200cm ±1%	
	Length: 15 - 25m/roll	
Weight	a. 1100-1300gsm with PVC cushion & nonwoven b. 900-1100gsm with PVC cushion	
Thickness	2mm	
Fungus test	ASTM G21 - 13	0 Grade
Abrasion (Martindale)	ISO 12947 - 2: 1998+ Cor.1: 2002	＞20000
Skew & bow	EN 427	<1%
Fire rate	ASTM E84 - 98	Class 1 or A
Classification For burning behavior of building materials and products	GB8624 - 2012	B2(D-s2, d0)
Light ageing test - UV exposure	ISO 4892 - 3: 2016 Cycle 1	Lamp type: UVA - 340, 1000h: Grade 4-5
Content of pentachlorophenol(PCP)	CEN/TS 14494	Not detected
Formaldehyde emission	EN 717 - 2	E1: 0.122mg/m3·h
Release of formaldehyde	EN15102:2007+A1:2011	E1: 3.5mg/kg
Heavy metals and specific elements		PASS
Release of vinyl chloride monomer		0.12mg/kg
DEHP, DBP, BBP, DIBP	REACH Annex XVII, Entry 51&52 , (EU) 2018/2005	PASS
Reach & RoHs	REACH REGULATION 211	PASS
	RoHs Directive 2015 863	
AZO	ISO 14362-1: 2017	PASS
Materials and articles in contact with foodstuffs	EN 1186: Part3	PASS
Tests for colour fastness	BS EN ISO 105 X12: 2016	Wet 4/5; Dry 4/5
Proposition 65	US California Proposition 65-Lead/Cadmium/Phthalate	ND

TECHNICAL INFORMATION
Structure: Woven vinyl with non-woven backing.
Light resistance: Good lightfastness
Fire classification: ASTM E84 - 98 Class A+
Maintenance: W-clean with water-based cleaner; Extra washable
Traffic: Heavyduty application; Water& Stain Repellent

HANGING RECOMMENDATIONS
Paste the wall using paste specially adapted for *nonwoven wallcovering*.
These hanging recommendations are given for information only. Detailed instructions are included in each order.
Paste the wall using pressure-sensitive adhesives for woven vinyl wallcovering ***without nonwoven backing or pvc cushion.***

Note 注意: This product is a simulation of natural materials, variations in Texture and Colour are inherent characteristics.
该产品模拟天然材质的纹理和颜色，其呈现的差异是产品之内在特性。

texlyweave®

we challenge the norms of weaving

Informed by continuous contact with designers and professionals in the textiles and interiors industry, we create, manufacture and distribute solutions to enhance new surface comfort of the spaces in which people live and work. **texlyweave®** products are technically sophisticated, sensitive, and hard-wearing. Their hallmark is the textile in which they are from wall to floor: **texlyweave®** is woven in our workshop in China in a palette of hundred colors. Since 2002, it has been our pride and delight to play our part in developing quality furniture and interior in China, Asia, Europe, the US, and beyond.

our woven vinyl from wall to floor with an exclusive texlyweave® creation

更多資訊，謹請垂詢！

For more information, please contact us at ***info@dragonshine.net****!*

EN 15102: 2007+A1:2011
157

FLIPHTML5

@texlyweave

© 2024 05 07 | Dragonshine - 20190901 - Any new version cancels and replaces this document

www.texlyweave.com